

REMARKS

This Preliminary Amendment presents a substitute specification, a new set of claims, and an amended Abstract for examination.


A marked-up version of the substitute specification, showing matter added to the translation by underlining and matter deleted from the translation by strike-through, is attached to this Preliminary Amendment. The substitute specification includes no new matter.

If there are any questions regarding this Preliminary Amendment or the application in general, a telephone call to the undersigned would be appreciated since this should expedite the prosecution of the application for all concerned.

If necessary to effect a timely response, this paper should be considered as a petition for an Extension of Time sufficient to effect a timely response, and please charge any deficiency in fees or credit any overpayments to Deposit Account No. 05-1323 (Docket # 095309.56147US).

Respectfully submitted,

April 22, 2005



Vincent J. Sunderdick
Registration No. 29,004

CROWELL & MORING LLP
Intellectual Property Group
P.O. Box 14300
Washington, DC 20044-4300
Telephone No.: (202) 624-2500
Facsimile No.: (202) 628-8844
VJS:ddd

Enclosures: Marked-Up Version of Substitute Specification
Clean Version of Substitute Specification
Abstract of the Disclosure

#369959

TITLE OF THE INVENTION

METHOD OF MONITORING A WEIGHT-SENSING SYSTEM

[0001] This application claims priority to International Patent Application No. PCT/EP03/011048, filed October 7, 2003, designating the United States of America, and German Application DE 102 49 440.1 filed on October 24, 2002, the entire disclosure of which is incorporated herein by reference.

BACKGROUND AND SUMMARY OF THE INVENTION

[0002] The invention relates to a method of monitoring the operatability of a weight-sensing system in a vehicle with at least one force sensor.

[0003] A trend has developed in recent years for controlling occupant protection systems in vehicles, particularly vehicle seat belts and air bags, by which the triggering characteristic of such safety devices is adapted to the occupant's weight by using a sitting weight measuring device as a weight-sensing system. Currently, force-sensitive foils are used in the seat area in vehicles of the applicant, which foils allow an approximate estimate of the occupant's body weight by way of the occupant's weight distribution.

[0004] The vehicle seat normally comprises seat rails, seat frames, a seat bucket and an adjusting mechanism. Since the occupants' load is transmitted to a vehicle chassis by the side frames and the seat rails, the side frames and the seat rails are subjected to the occupants' weight. Force sensors are therefore used ~~such~~ for measuring the total weight of the vehicle seat ~~that they~~. The force sensors are positioned at the upper or lower surfaces of the seat rails or sections of the side frames.

[0005] An occupant weight sensor therefore should have ~~precision with respect to the precise~~ detection as well as stability. For example, a strain gauge force transducer and an inductive force sensor are known from German Patent Document DE 44 20 691 C1. The ~~former strain gauge~~ transduces the surface

elongation of an elastic body generated by the force to be measured into an ohmic resistance change of strain gauges which are then processed by the signal processing of the balance. In the case of the inductive force sensor, a weight acting upon a measuring cell generates an elongation of a ferromagnetic tension rod enveloped by means of a coil. In this case, the inductivity of the coil is reduced which results in an increase of the frequency of an oscillator connected on the output side. A conclusion is drawn with respect to the weight from the frequency change.

[0006] As a result of a strong shock or in the event of an impact, a so-called crash, the weight-sensing system may be detuned by the acting forces, for example, by shearing forces such that a new adjusting or calibration of the entire weight-sensing system is required. The operatability of the weight-sensing system is ~~of decisive significance~~ important for the functioning of the occupant protection systems and thus for the occupants' safety.

[0007] It is now an object of the invention to provide a method of monitoring the operatability of a weight-sensing system in the vehicle which ensures a reliable detection of a possible failure of the weight-sensing system.

~~This object is achieved by a method of monitoring the operatability of a weight-sensing system having the characteristics of Claim 1.~~

[0008] According to the invention, the weight-sensing system emits a warning message when a defined value - a threshold value - for the force acting upon a force sensor is exceeded, which warning message ~~points to~~ indicates a possible damage to the weight-sensing system. In the event of strong shocks caused, for example, by an extreme pothole in the road surface, or in the event of an impact, high forces act upon the force sensor and thus upon the weight-sensing system, which may result in a failure of the weight-sensing system. The defined value for the force acting upon the force sensor is therefore selected such that its magnitude corresponds to the values which occur in the event of violent shocks. The occupants of the vehicle are informed in time concerning a possible failure of the weight-sensing system and, for checking the weight-sensing system, can immediately take the vehicle to a repair shop since a failure of the weight-

sensing system can also lead to functional disturbances in the operation of the occupant protection system. This improves the occupant protection.

[0009] In a further development, in the event of an impact of the motor vehicle, the warning message is emitted by an impact sensor of the vehicle which senses the impact and which is not the weight-sensing system. The reliability of the detection of a possible failure of the weight-sensing system is thereby further increased and designed to be independent of the weight-sensing system itself. Particularly when the defined value for the force acting upon the force sensor of the weight-sensing system in the event of an impact of the vehicle is not reached, the warning message can be emitted by an occupant protection system sensing the impact.

~~Additional advantageous further developments of the invention are indicated in the subclaims~~

[0010] Other objects, advantages and novel features of the present invention will become apparent from the following detailed description of the invention when considered in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWING

[0011] ~~The invention will be explained in detail by means of several embodiments in the single figure. This~~ The sole figure shows a ~~cutout of a~~ block diagram of the system description for a method of monitoring the operatability of a weight-sensing system in a vehicle.

DETAILED DESCRIPTION OF THE DRAWING

[0012] According to the figure, the block diagram of a weight-sensing system of a four-seat vehicle comprises force sensors 2, 4, 6, 8 which are arranged in the vehicle corresponding to the distribution of the front and rear seats. As a rule, the weight-sensing system has a number of force sensors 2, 4, 6, 8 corresponding to the number of seats. Strain gauge force transducers, inductive sensors and/or piezoelectric sensors can be provided as the force sensors 2, 4, 6, 8. However, other sensors are also suitable for use in the weight-sensing system. The force

sensors 2, 4, 6, 8 each ~~comprise~~include an amplifier with a signal filter as well as an analog-to-digital converter. The detected measured values are temperature-compensated and transmitted by way of three-wire lines 10 to a control unit 12 of the weight-sensing system. The three-wire lines 10 permit a grounding, a power supply of the force sensors 2, 4, 6, 8 ~~as well as and~~ a bidirectional data exchange with the force sensors 2, 4, 6, 8.

[0013] All occupant-related weights are detected by means of the force sensors 2, 4, 6, 8. In addition, the position of the mass center of gravity is determined for each seat. In addition to the weights acting upon the seat bucket, the weights ~~exercised~~acting upon the seat backrest are also taken into account. Further, additionally acting forces which cannot be assigned to an occupant's weight are corrected in the control unit 10 in order to be able to determine the occupants' weight as precisely as possible. For example, a force diversion by way of the legs is corrected by taking into account the mass center of gravity. Jammed-in objects under the seat, which falsify the actual weight, can be compensated by way of suitable covering measures or intelligent algorithms. Occurring lateral forces can be compensated by the further development of the force ~~sensor~~sensors 2, 4, 6, 8 or by a more suitable application. Undesirable forces caused by vibrations during the driving operation on a rough route are filtered out.

[0014] A precise weight sensing of the occupants is required for an individual person-related controlling of the occupant protection system. A resolution in the kilogram range is required in order to be able to differentiate between defined weight classes with different triggering conditions. For, example, at a weight lower than 35 kg, a safety air bag should not be triggered. This weight class may involve a child or a child with a child seat. In this weight class, a triggered air bag may lead to injuries in a wrong sitting position. At a weight of over 40 kg - the weight of a light adult -, a triggering will, in turn, be necessary. The inflating pressure of the air bags as well as the contact pressure of the seat belts are adjusted as a function of the weight class and therefore require the continuous readiness of the weight-sensing system. A failure of the weight-sensing system leads directly to a safety risk for the occupants.

[0015] In the case of a method of monitoring the operatability of the weight-sensing system, the weight-sensing system emits a warning message when a threshold value for the force acting upon the force sensor 2, 4, 6, 8 is exceeded, which warning message points to possible damage to the weight-sensing system. The warning message contains a notice for the driver of the vehicle that he should drive to a repair shop for checking in order to check the weight-sensing system. Even in the event of violent shocks which ~~do~~are not ~~have to be~~ necessarily caused by an impact, the weight-sensing system could be damaged. The threshold value for the force acting upon the force sensor 2, 4, 6, 8 should be clearly above the weight of the respective occupant. The shock-caused possible failure of the weight-sensing system above a threshold value for the force acting upon the force sensor 2, 4, 6, 8 is indicated immediately. The occupants' safety is considerably improved by this method.

[0016] In addition, in another embodiment, in the event of an impact of the motor vehicle, the warning message is emitted by an impact sensor of the vehicle sensing the impact, which impact sensor may be formed by an acceleration sensor. This additionally increases the safety of the occupants of the vehicle. It is definitely possible that, during an accident, no forces are detected by the weight-sensing system which exceed the threshold value for the force acting upon the force sensor 2, 4, 6, 8, if this force acts, for example, perpendicularly with respect to the sensing direction, and damage to the weight-sensing system has nevertheless taken place. For this reason, in this embodiment, the impact is detected independently of the weight-sensing system, by another system which is not shown. In particular, when the defined threshold value for the force acting upon the force sensor 2, 4, 6, 8 is not reached, in the event of an impact of the vehicle, the warning message can be emitted by the occupant protection system sensing the impact. The impact can also be sensed by other systems, for example, by a system for detecting the ranging range of motion.

[0017] The warning message generated by the weight-sensing system in the event of a demand, is made available for further usage purposes on a CAN (car area network)-bus 14 - an information channel conceived especially for the

vehicle operation -, or in fault memories. The CAN bus also contains, for example, ~~also~~ information concerning the opening condition of the doors, the usage of seat belts, the weight classification and other diagnostic units.

[0018] Among other things, the warning message is displayed in a combination instrument in the vehicle occupant compartment, which is not shown in detail~~[[,]]~~~~the~~. The warning message ~~being~~is implemented in the form of a text message and/or as a further development of an indicator lamp. If the warning message is filed in a fault memory, the warning information can be read out in a diagnostic unit.

[0019] By means of the indicated method, an almost complete checking or monitoring of the weight-sensing system is ensured even when values for internal defect parameters are not exceeded. By means of the display of the fault message for the weight-sensing system, a possible malfunctioning of the occupant protection system is also ~~pointed out~~indicated.

[0020] The foregoing disclosure has been set forth merely to illustrate the invention and is not intended to be limiting. Since modifications of the disclosed embodiments incorporating the spirit and substance of the invention may occur to persons skilled in the art, the invention should be construed to include everything within the scope of the appended claims and equivalents thereof.

ABSTRACT OF THE DISCLOSURE

A process for monitoring the operability of a weight-sensing system in a vehicle with at least one force sensor (2, 4, 6, 8). The weight-sensing system emits a warning message when a threshold value for the force acting upon the force sensor (2, 4, 6, 8) is exceeded. The warning message indicates a possible damage to the weight-sensing system. This measure ensures a reliable detection of a possible failure of the weight-sensing system.